



شرکت صنعتی و شیمیایی نگین زره پارسیان

NEGIN ZEREH PARSIAN

تولید کننده رنگهای صنعتی، ساختمانی، دریایی و چوب
Industrial, Construction, Marine and Wood Paints

ROOF COATING NP-2249

Product Description

NP-2249 is a high-build acrylic roof coating which forms a highly durable elastomeric membrane with UV resistance, flexibility and water proofing properties.
Also, can be used to fill cracks and holes in concrete.

Technical Data

Color	Upon request
Solid by volume	53±2%
Specific Gravity	1.40±0.10 g/cm ³
Recommended D.F.T	500 μ ≤
Shelf life	12 months at 25°C
Package	10-liter containers

Recommended Use

Ideal as roof coating or various exterior top sides of construction Projects.

Application Details

Application method	Brush, Roller
Surface temperature	10-40°C
Thinner/cleaner	Fresh water
Application Condition	Surface temperature must at least of 3°C above the dew point. Relative humidity shall not exceed 85%. Do not apply the next coat unless the previous one is fully dry.

Outstanding Characteristics

- Waterproofing and excellent water resistance
- Excellent flexibility
- Adheres firmly to facade surfaces including concrete.
- Easy to apply

Surface Preparation

All surfaces to be coated shall be clean, dry and free from oil, grease, and other contaminants.
Remove loose material for example laitance and Concrete must cure completely; for 28 days minimum.
Moisture content in the surface must be below 4%.
Apply sealer prior to application NP-2249.

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Neginzereh-pars Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Neginzereh-pars representative to obtain the most recent Product Data Information and Application Bulletin. The Neginzereh-pars Company warrants our products to be free of manufacturing defects in accord with applicable Neginzereh-pars quality control procedures.

Rev. 01 | 2026



کارخانه: ۱۱۰ اتوبان تهران - قزوین، روبری نیروگاه شهید رجایی
شهرک صنعتی کاسپین، فاز ۳، بلوار شهید رجایی غربی، خیابان ارکیده ۲
تلفن: ۰۲۸ - ۳۲۸۴۹۲۰۱ | فکس: ۰۲۸ - ۳۲۸۴۸۵۴۰

Website : www.neginzereh.com | Email : info@neginzereh.com

دارنده گواهینامه های ISO 9001:2008, ISO 14001:2004 و OHSAS 18001:2007 از TUV NORD آلمان

دفتر مرکزی: تهران، شهرک غرب، بلوارفرحزادی، خیابان ارغولن غربی (شهید حافظی) نبش کوچه پرتو
پلاک ۲۹-۳۱، طبقه سوم، واحد ۷ | تلفن: ۰۲۱ - ۲۲۱۳۹۱۳۰ - ۴۹ | فکس: ۰۲۱ - ۲۲۱۳۹۱۵۰

Head Office : Unit 7, Third Floor, No.29-31, Corner of Parto Alley, West Arghavan St.,
Farahzadi Blvd, Shahrak-e Garb,Tehran. IRAN Tel : (+9821)22139130 - 49 Fax : 22139150