



**NEGIN ZEREH Co.**

Industrial, Marine, Water Base, Architectural Paint

## ACRYLIC EMULSION COATING NZ-135

### Product Description

**NZ-135** is a single pack high-performance water-based acrylic coating.

### Recommended Use

This coating can be used as a protective and decorative coating on wood and concrete surfaces and other masonry substrates, especially in aggressive, polluted and coastal environments.

### Outstanding Characteristics

- Excellent adhesion
- Excellent water resistance
- Good weather resistance
- Good UV resistance
- Good flexibility & decorative appearance

### Surface Preparation

The surface must be clean, dry and free from any contamination such as grease, salt and loose paint.

### Technical Data

Finish	Matt,Semi-gloss, Gloss
Color	Upon request
Solid by volume	22±3%
Specific Gravity	1.15±0.10 gr/cm <sup>3</sup>
Recommended D.F.T.	40-60 microns
Theoretical coverage	5.0-3.0 m <sup>2</sup> /L
	Practical coverage depends on loss factor
Touch dry	30 min. at 20°C
Hard dry	5 hrs. at 20°C
Shelf life	12 months at 25°C
Package	4 & 10 liter container

### Application Details

Application method	Air spray, Brush ,Roller
Surface temperature	10-45 °C
Mixing ratio	Single Pack
Thinner/cleaner	Water
Pot Life	N/A
Recoat interval	Min 5 hrs. at 20°C
	Max indefinite
	Recoating intervals related to later conditions of exposure

**Note:** Film thickness may be specified in another film thickness than indicated depending on purpose and area of use. This will alter the spreading rate and may influence the amount of thinning necessary, drying time and recoating interval.

**Safety:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Neginzereh-pars Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Neginzereh-pars representative to obtain the most recent Product Data Information and Application Bulletin. The Neginzereh-pars Company warrants our products to be free of manufacturing defects in accord with applicable Neginzereh-pars quality control procedures.