



**NEGIN ZEREH Co.**

Industrial, Marine, Water Base, Architectural Paint

# ALKYD HIGH GLOSS TOPCOAT NZ-208

## Product Description

**NZ-208** is a general purpose glossy topcoat based on medium oil Alkyd resin, which form a weather resistant coating.

## Recommended Use

As a high gloss finish coat over alkyd primed industrial steel surfaces such as industrial engines, automobiles, wagons, containers etc.

## Outstanding Characteristics

- High gloss and color retention
- Fast drying
- Excellent spray ability
- Good oil resistance
- Good resistance in mildly to moderate corrosive environment

## Surface Preparation

The surface must be undamaged, dry and free from any contamination such as grease, dust, salt and loose paint.

## Technical Data

Finish	Gloss, High-gloss
Color	Upon request
Solid by volume	50±3%
Specific Gravity	1.10±0.10 gr/cm <sup>3</sup>
Flash point	30 °C
Recommended D.F.T.	40-60 microns
Theoretical coverage	11.0-7.8 m <sup>2</sup> /kg Practical coverage depends on loss factor
Touch dry	2 hrs. at 20 °C
Hard dry	16 hrs. at 20 °C
Thermal resistance	Max. 120 °C (dry exposure) Non-Continuous Max130 °C
Shelf life	12 months at 25 °C
Package	20 liter container

## Application Details

Application method	Air/Airless spray, Brush ,Roller
Surface temperature	10-45 °C
Mixing ratio	Single pack
Thinner/cleaner	NZT-200/2
Pot Life	N/A
Recoat interval	Min 16 hrs. at 20 °C Max 30 days at 20 °C Recoating intervals related to later conditions of exposure
Nozzle orifice	0.013"-0.015"
Nozzle pressure	100 bar/1450 psi Airless spray is indicative and subject to adjustment
Application condition	Apply only on a dry and clean surface with a temperature 3 °C above the dew point to avoid condensation. In confined spaces provide adequate ventilation during application and drying.

**Note:** Film thickness may be specified in another film thickness than indicated depending on purpose and area of use. This will alter the spreading rate and may influence the amount of thinning necessary, drying time and recoating interval.

**Safety:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Neginzereh-pars Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Neginzereh-pars representative to obtain the most recent Product Data Information and Application Bulletin. The Neginzereh-pars Company warrants our products to be free of manufacturing defects in accord with applicable Neginzereh-pars quality control procedures.