



NEGIN ZEREH Co.

Industrial, Marine, Water Base, Architectural Paint

ALKYD CHLORINATED RUBBER TRAFFIC PAINT NZ-212

Product Description

NZ-212 is a quick drying paint based on alkyd - modified chlorinated rubber traffic paint.

Recommended Use

Suitable for use on asphalt, concrete, and especially for road marking and airports Site.

Outstanding Characteristics

- High abrasion Resistance
- Excellent water and alkali Resistance
- High Adhesion to concrete and Asphalt
- Very high Reflective properties with glass beads
- Very good whiteness property

Surface Preparation

The surface must be undamaged, dry and free from any contamination such as grease, dust, salt and loose paint.

Technical Data

Finish	Flat, Semi-flat
Color	White
Solid by volume	40±3%
Specific Gravity	1.35±0.10 gr/cm ³
Flash point	24 °C
Recommended D.F.T.	100-150 microns
Theoretical coverage	3.0-2.0 m ² /kg Practical coverage depends on loss factor
Touch dry	20 min. at 20 °C
Hard dry	45 min. at 20 °C
Fully cured	24 hrs. at 20 °C
Shelf life	12 months at 25 °C
Package	20 liter container

Application Details

Application method	Automatic / hand spray set
Surface temperature	10-45 °C
Mixing ratio	Single Pack
Thinner/cleaner	NZT-400
Pot Life	N/A
Recoat interval	Min wet on wet Max indefinite
Application condition	Apply only on a dry and clean surface with a temperature 3 °C above the dew point to avoid condensation. In confined spaces provide adequate ventilation during application and drying.

Note: Film thickness may be specified in another film thickness than indicated depending on purpose and area of use. This will alter the spreading rate and may influence the amount of thinning necessary, drying time and recoating interval.

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Neginzereh-pars Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Neginzereh-pars representative to obtain the most recent Product Data Information and Application Bulletin. The Neginzereh-pars Company warrants our products to be free of manufacturing defects in accord with applicable Neginzereh-pars quality control procedures.